

SR15

Silicone Thin Coat Render
Anti-Crack




Highly
Flexible

Anti-Crack

Silicone Water
Repellent

Highly
Breathable

UK CA Declaration of Performance

	<p>Wetherby Laroc Group Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE 14</p>
<p>ecorend SR15 Silicone Thin Coat Render</p> <p>Water diluted external render based on organic binder</p> <p>EN 15824:2017</p>	
Water vapour permeability	V2 (Medium)
Water absorption	W3 (Low)
Adhesion	> 0.3MPa



Low Maintenance, Weatherproof, Textured Silicone Render

ecorend SR15 Silicone Thin Coat Render, is a ready to use, through coloured, flexible thin coat render. Developed using high-performance silicone technology ensures that the finish is highly water repellent, highly vapour permeable and extremely flexible, giving the very best resistance to cracking. This product can be applied by hand or spray and must be used as the topcoat in the SR15 system.

Approvals and Certificates

BBA approved system – 18/5592 & EN 15824:2017

Technical Data

Pack Size	25kg Bucket
Finishing Tool	Plastic Float
Substrate Primer	ecorend SP15 Silicone Primer
Suitable Substrate	ecorend Base Coat/Sponge Float Finish
Dilution Rate	Max 2%
Ready to Finish	10 to 40 minutes @ +5°C to 25°C
Humidity Requirement	Less than 85% for a minimum of 24 hours
Coverage	Approx. 8 to 10m ² per 25kg
Application Temperature	+5°C to 25°C for a minimum of 24 hours

